

PRESIDENT WASHINGTON MB8719 (11.1125) (CONT)

L13 is VCO adjustment.

Readjust L26, L27, L28, L29, L36 as necessary for the  
26.815-28.045 coverage.

Remove TR32.....AMC/ALC limiter.

Remove C81, near IC3.

Replace R84 with a 47K ohm resistor.

VR2.....SQ range.

VR1.....Signal meter.

RT301.....Voltage regulator.

VR12.....Modulation meter.

VR8.....35ma idle current for USB.

VR9.....45ma idle current for USB.

VR5.....Carrier balance.

VR10.....AM power.

PRESIDENT McKINLEY (1011001) 8719 w/11.1125

Channel Modification- use update in this volume, pages 25-27.

Clarifier-

1. Remove R415 and install a jumper in it's place.
2. Clip R187.
3. Clip D36.
4. Remove C132, if present.
5. For more slide, install a Super Clarifier Diode at D37.
6. Cut the ORANGE wire off of the Clarifier.
7. Run a new wire from the Clarifier to pin 1 of IC5, CT3,  
USB; L20 AM; L19 LSB. Widebanding: Remove C81; Change  
R84 to a 47K ohm resistor. Readjust VR5 for carrier null  
on SSB. Remove TR32 for maximum modulation. VR6 is  
for AM Power. The VCO is L13.