

SPECIFIC RADIO TUNE-UPS (Cont'd):

SEARS 934.38062700

RX: RT1 - Mixer gain (cute term! really AGC)  
RT2 - S meter adjust  
TX: Peak - T11, T12, T13, T14, T15  
RT3 - RF meter adjust  
Modulation defeat - D7; no AMC adjust. If defeated, change final  
to 2SC1306.

TEABERRY T CHARLIE (4010)

RX: VR1 - AGC  
VR3 - Squelch range  
VR4 - S meter adjust  
TX: Peak - L901, L903, L905  
VR7 - AMC (Defeat C507; see note)  
VR5 - RF meter adjust  
NOTE: If defeat AMC, change final to 2SC1306 and heat sink the  
driver - even if you don't change it.

TEABERRY STALKER VIII

RX: VR3 - Squelch range  
VR4 - S meter adjust  
TX: Peak - L10, L11, L15  
VR5 - RF meter adjust  
AMC Defeat - C-49, electrolytic capacitor.

TEABERRY STALKER IX

NOTE: See Vol. 4, pp. 7,8 of Secret CB for frequency & slide mod.  
RX: VR2 - Squelch range  
VR1 - S meter adjust  
TX: Peak - (In this order) L, 26, L27, L28, set VR7 to minimum  
Peak - in USB L29, L36  
VR8 - Driver bias  
VR9 - Final bias  
VR5 - Carrier bias  
VR7 - ALC  
VR6 - AM Power  
VR10 - TX Meter adjust  
CAUTION: Unit only has 20W final!

TENNA 10902

RX: R94 - Squelch range  
R28 - S meter adjust  
TX: Peak - T11, T12, T13, T14, T15, T16, L4  
R71 - AMC  
R90 - RF meter adjust  
R132 - SWR meter calibrate