

SPECIFIC RADIO TUNE-UPS

AR 711: President:

RX: Adjust L1, L2, L3, L4, L5, L6, L7 for max. on Ch. 19.
VR4; Squelch
VR1; S-Meter-adjust for S-9 with 100 UV input.

TX: Peak L17, L18, L10, L14 on Ch. 19.
VR5; A.M.C.
VR3; RF Pwr. Meter.

American Motors 3231847/48/49/50:

RX: VR102; Squelch Range.
VR101; S Meter.

TX: Peak F1L, T301, L302, L304, L305, L306
VR301; RF Power.
VR303; AMC
VR320; RF Power Meter.

Cobra 19GTL TC9109P:

RX: VR7; RF Gain.
VR3; SQ Range.
VR4; S Meter.

TX: Peak L10, L11, L12, L15
VR6; AMC
VR5; RF Power Meter.

Cobra 45XLR (MPD858):

TX: Peak L111, L113, L110
RV105; AM Mod.

For Channels 41-66, raise pin 19 to 5V.

DAK Mark V MM55116N:

RX: RV101; Squelch Range
RV102; S Meter

TX: Adj. L402, L302, L303, L304, L305, L306, L307, and L308 for
Max. RF output.
RV301; RF Power Meter.
RV202; AMC or remove Q202.
L403 VCO coil.