



SEMICONDUCTOR	TERMINAL CONNECTION	(BOTTOM VIEW UNLESS OTHERWISE NOTED)	SIDE VIEW
2SA719	ECB	ECB	ECB
2SC828	BCE	BCE	BCE
2SC829	BCE	BCE	BCE
2SC839	BCE	BCE	BCE
2SC948	BCE	BCE	BCE
2SC918	BCE	BCE	BCE
2SC359	BCE	BCE	BCE
2SC1047	BCE	BCE	BCE
2SC1215	BCE	BCE	BCE
2SC710	BCE	BCE	BCE
2SC784	BCE	BCE	BCE
2SC372	BCE	BCE	BCE
2SC1687	BCE	BCE	BCE
2SC1688	BCE	BCE	BCE
2SC1306	BCE	BCE	BCE
2SC1678	BCE	BCE	BCE
2SC1816	BCE	BCE	BCE
2SD313	BCE	BCE	BCE
2SC1957	BCE	BCE	BCE
TA7205P	BCE	BCE	BCE
BA521	BCE	BCE	BCE

**NOTES:**

1. All resistors are 5%, 1/4 watt, with value given in ohms, unless specified otherwise.
2. All capacitor values are given in uF, unless specified otherwise.
3. Symbols used:  
 -chassis ground  
 -p.c. board ground  
 -indicates component value may vary from unit to unit

Figure 2-13. Schematic Diagram, Model 3084B