



POWER PLUG CONNECTIONS

- 115 VAC 150-174
115 VAC to pins 1 & 4
Jumper pins 2 to 3
13 to 18
- 6 VDC, NEG. GND. 150-212
+6VDC Hot to pin 1 (red)
-6VDC Gnd to pin 15 (brown)
Jumper pins 11 to 12 to 14 to 15 to 18
2 to 5 to 17
7 to 8
6 to 9
10 to 16
- 6VDC, POS. GND. 150-213
-6VDC Hot to pin 1 (brown)
+6VDC Gnd to pin 15 (red)
Jumper pins 9 to 12 to 15 to 18
6 to 11 to 14
2 to 5 to 17
7 to 8
10 to 16
- 12 VDC, NEG. GND. 150-214
+12VDC Hot to pin 1 (red)
-12 VDC Gnd to pin 15 (brown)
Jumper pins 10 to 14 to 15
7 to 8 to 16
2 to 5 to 18
6 to 9
- 12 VDC, POS. GND. 150-215
-12 VDC Hot to pin 1 (brown)
+12 VDC Gnd to pin 15 (red)
Jumper pins 6 to 10 to 14
7 to 8 to 16
2 to 5 to 18
9 to 15

EXECUTIVE
Model 100 D
SERIES 2/12/63 (REVISED 7-68) APPROVED BY
SER. 2/12/63 SER. 3/12/63
INTERNATIONAL CRYSTAL MFG. CO., INC.
P. O. BOX 100, CHICAGO, ILL. 60601